

# DOOR CANOPIES

## FOR STEEL BUILDINGS



*Picture shows upgraded lighted canopy*

**Rated for up to 140 MPH Wind Speeds and 100 LB Snow Loads**

### Construction:

- Economical and Attractive Overhead Protection From the Elements
- 24 Flat Soffit & Integral Gutter with Rear Mounted Drains
- 16 Gauge Galvanized Internal Frame
- 18 Gauge Telescoping Support Channels which Mount Behind Wall Panel Between Girts.
- Mounting Clips & Fasteners Included: 1/2" or 3/4" Pipe Hangers with Adjustable Rod Ends

### Finishes:

- Galvalume Steel
- All Standard Metal Building Colors Available
- Custom Color Matching

### Sizing:

- Single Door 4'6" x 4'0"
- Double Door 7'6" x 4'0"
- Available in 3'0" & 5'0" Projections
- Mulling Options Available for Continuous Run Applications

### Design Specifications:

- Exposure Category 'B.'
- Importance Factor,  $I = 1.0$
- Topographic Factor  $K_{zt} = 1.0$
- Wind Directionality,  $k_d = 0.85$

### Options:

- Lights Installed on Underside of Canopy
- Masonry Mount (Anchors by Others)
- Downspouts
- Many Others Upon Request

# STANDARD COLOR CHART



COCO BROWN



KOKO BROWN



DEEP RED



HAWAIIAN BLUE



COLONIAL RED



SAHARA TAN



LIGHT STONE



SANDSTONE



SIERRA GOLD



PATRICIAN BRONZE



POLAR WHITE



ASH GREY



KELLY GREEN



GALVALUME



REGAL BLUE



FERN GREEN